



Child Center Product Specification

Blow Molded Plastics

All Blow Molded Products are manufactured from high-density polyethylene. The nominal wall thickness will be .200". All blow molded products shall meet or exceed the following specification:

ASTM-D 1248 Type III, Class A, Category 5; Melt Index (ASTM D-1238); Density (ASTM D1505); Tensile Values (ASTM D-638); Flexural Modulus (ASTM D-790); IZOD Impact Strength (ASTM D256); Brittleness Temperature (ASTM D746).

Hardware

All nuts, bolts, and washers, with exceptions noted, shall be stainless steel Grade 304 in varying lengths, with a vandal-resistant button-pinned head configuration and factory-applied locking patch. When allowed a 72-hour cure time, the locking patch will prevent the bolt from loosening without at least 4 times the installation torque. Qitele USA will supply the special tool required to turn vandal-resistant hardware with each shipment.

Uprights - Steel

The posts shall be 2 3/8" O.D. 12 – gauge galvanized steel tubing.

Child Center Warranty

Three Year (3) Limited Warranty on Child Center units, all models.

KidsTale warrants to its original customer for as long as the original customer owns the product and uses the product with normal use and installation in accordance with published specifications to be free from defects in materials and workmanship.

This warranty does not cover damage from misuse, vandalism, modified parts or damage such as dents, scratches, fading/weathering and normal wear and tear.

Warranty claims must be filed within the applicable warranty period. Warranty replacement parts do not include shipping cost or the cost of labor for part replacement. Replacement parts carry the applicable warranty from the date of shipment of the replacement part.